



000 -1.5 ° CAMBER **WASHERS** AR ΙΟ RIDE HEIGHT 25 mm TOE-IN (+) / OUT (-) __0 ° BUMP STEER SPACER ___3 AXLE HEIGHT CASTER □up □20° □ 25° □down **☑** 30° **FRONT SHOCKS** OIL 30 wt SPRING (color) _____Brown PISTON # ____2 SHAFT ☑ unobtainium ☐ STD # LIMITERS ___1 FRONT TIRES & WHEELS FRONT TIRES 7207S INSERTS Full Stock WHEELS Associated

000 #WASHERS -1.5 ° CAMBER ABC 000 ΙO RIDE HEIGHT 25 mm **ANTI-SQUAT** ANTI-ROLL BAR □0° ✓ none ☐ black (soft) □ 1° ☐ sivler (med) gold (heavy) **WHEELBASE □**3° □ long ☐ short **REAR SHOCKS** OIL 25 wt PISTON # ____2 SPRING (color) ____ Green SHAFT ☑ unobtainium ☐ STD # LIMITERS ___1_ **REAR TIRES & WHEELS** REAR TIRES Red BK Bar INSERTS Proline 2-Stage WHEELS Associated

RADIO/BATTERIES	MOTOR	OTHER
RADIO Airtronics M11 SERVO XP 1015	MOTOR & WIND LRP X-12 8.5	BODY JConcepts Scoopless Illuzion
ESC LRP Sphere Comp '07 (1/1/0/1)	BRUSHES Timing = 4 Dot	WING Associated B44 6.5"
DRAG BRAKE 1 INIT BRAKE 0	SPRING Rotor = 12.0 mm	WING ANGLE ☐ 0° ☐ 3° ☑ 6°
BATTERY PLACEMENT ☑ front ☐ rear	PINION / SPUR <u>22</u> / <u>78</u>	CHASSIS Plastic
BATTFRIFS Reedy 35C 5000 Lipo (#709)		

smooth bumpy low traction med traction high traction	
wet	✓ dusty

☐ other

✓ dry

CONDITIONS

COMMENTS

TRACTION COMPOUND ____

CVDs; Car at minimum ROAR weight; Everything graphite except chassis; 1 oz of weight next to receiver; 4th hole for rear shock drilled in tower

FOR MORE SETUPS, VISIT www.RC10B4.com and click on "SETUPS"