

**Front Suspension:**

Reset Forms

|                             |  |
|-----------------------------|--|
| <b>Ride Height:</b>         | 20 mm  |
| <b>Camber:</b>              | -1   |
| <b>Toe:</b>                 | 0° (Tierod Gap = 27.5 mm)  |
| <b>Anti-Roll Bar:</b>       | None   |
| <b>Arm Type:</b>            | #91674 Gullwing, Hard  |
| <b>Tower Type:</b>          | #91768 Gullwing  |
| <b>Caster Block Insert:</b> | 5°   |
| <b>Steering Block:</b>      | 4 mm   |
| <b>Bulkhead Type:</b>       | #91658 FT Aluminum   |
| <b>Kick-Up Angle:</b>       | 25°  |
| <b>Wheel Hex:</b>           | #91682 Aluminum  |
| <b>Notes:</b>               | #1366 FT Aluminum Servo Horn, 25T<br>#91668 FT Aluminum Bellcranks |

**Bump Steer Spacing:** 0 mm

**Steering Plate:** #91680 +1

**Steering Stop Spacing:** 0 mm

**Axle Height:** +2 mm

**Caster Block Spacing:** 1 mm

**Ball Stud Spacing:** 1 mm

**Ball Stud Spacing:** 1 mm

**Ball Stud Spacing:** 1 mm

**Ball Stud Spacing:** 1 mm

**Rear Suspension:**

|                                 |   |
|---------------------------------|---|
| <b>Ride Height:</b>             | 20 mm   |
| <b>Camber:</b>                  | -1°   |
| <b>Anti-Roll Bar:</b>           | None  |
| <b>Arm Type:</b>                | #91853 73 mm, Standard  |
| <b>Arm Spacing:</b>             | Forward (2 mm Behind Arm)   |
| <b>Hub Spacing:</b>             | Forward <input type="checkbox"/> Middle <input checked="" type="checkbox"/> Back <input type="checkbox"/> |
| <b>Shock Mounting Position:</b> | Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>                     |
| <b>Tower Type:</b>              | #91769 Standard   |
| <b>Wheel Hex:</b>               | #91610 FT Clamping, 7.0 mm  |
| <b>CVA Bone Length:</b>         | #91434 67 mm  |
| <b>CVA Axle:</b>                | #91859 +2 mm  |
| <b>Notes:</b>                   |   |

**C Mount:** Aluminum  Brass

**D Mount:** Aluminum  Brass

**Possible Insert Locations**

**Camber Link Spacing:** 2 mm

**Ball Stud Spacing:** 2 mm

**Ball Stud Spacing:** 3 mm

**Hub Insert:** +3  +2  +1  0

**Electronics:**


|   |                                   |
|---|-----------------------------------|
| <b>Radio:</b> Futaba 7PX  | <b>Servo:</b> #27109 Reedy RT1408 |
| <b>EPA: Throttle:</b> 100 %   | <b>Brake:</b> 100 %               |
| <b>ESC:</b> #27004 Reedy Blackbox 510R                                    |                                   |
| <b>ESC Settings:</b> See Baseline Setup Sheet                             |                                   |
| <b>Motor:</b> Reedy Sonic M4 + #27447 Reedy 540-M4 Rotor (12.5x7.25x25.3) |                                   |
| <b>Wind:</b> #27441 7.5T  | <b>Timing:</b> 20°                |
| <b>Pinion:</b> 22   | <b>Spur:</b> 78                   |
| <b>Battery:</b> #27347 Reedy Zapper SG3 6100 mAh 85C                      |                                   |
| <b>Battery Position:</b> 4F   |                                   |
| <b>Battery Weight:</b> #27304 Reedy 22g Under Battery                     |                                   |

**Drivetrain:**

|  |   |
|--|---|
| <b>Transmission:</b>                               | <b>Laydown:</b> <input checked="" type="checkbox"/>   |
| <b>3 Gear:</b> <input checked="" type="checkbox"/> | <b>Layback:</b> <input type="checkbox"/>              |
| <b>4 Gear:</b> <input type="checkbox"/>            | <b>Stand Up:</b> <input type="checkbox"/>             |
| <b>Differential:</b>                               | <b>Ball Diff:</b> <input checked="" type="checkbox"/> |
| <b>Height:</b> 2                                   | <b>Gear Diff:</b> <input type="checkbox"/>            |
| <b>Gear Diff Mass:</b>                             |   |
| <b>Notes:</b>                                      |   |
| <b>Slipper Clutch:</b>                             |   |
| <b>Type:</b> #91802 & #91806 FT Vented Slipper Hub |   |
| <b># of Pads:</b> 2 x #91197 FT LCF                |   |

**Shocks:**

|                       | Front   | Rear                          |
|-----------------------|---|-------------------------------|
| <b>Piston:</b>        | 1x1.6+1x1.7 FT Flat Machined                        | #91627 2x1.7 FT Flat Machined |
| <b>Fluid:</b>         | #5432 32.5 wt                                       | #5422 30 wt                   |
| <b>Spring:</b>        | #91329 V1 Gray                                      | #91337 V1 White               |
| <b>Int. Limiters:</b> | 0   | 0                             |
| <b>Ext. Limiters:</b> | 0   | 0                             |
| <b>Stroke:</b>        | 22.5mm  | 28mm                          |
| <b>Eyelet Length:</b> | Long  | Long                          |
| <b>Cup Offset:</b>    | 5 mm  | 5 mm                          |
| <b>Notes:</b>         | #91494 Machined Shock Spacers V2; #91493 FT X-Rings |                               |



**Track Info:**

|  |
|--|
| <b>Size:</b> Small <input type="checkbox"/> Medium <input checked="" type="checkbox"/> Large <input type="checkbox"/> Extra Large <input type="checkbox"/>   |
| <b>Surface:</b> Dirt <input checked="" type="checkbox"/> Carpet <input type="checkbox"/> Astroturf <input type="checkbox"/> Multi Surface <input type="checkbox"/>   |
| <b>Traction:</b> Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input checked="" type="checkbox"/>  |
| <b>Moisture:</b> Dry <input checked="" type="checkbox"/> Damp <input type="checkbox"/> Wet <input type="checkbox"/>  |
| <b>Condition:</b> Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input checked="" type="checkbox"/> Hard Packed <input checked="" type="checkbox"/><br>Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/> |
| <b>Temperature: Ambient:</b> 60F <b>Track:</b> 60F   |
| <b>Notes:</b>  |
| <b>Vehicle Comments:</b> #91652 Side Rails, Standard; #91616 & 91620 Chrome Shock Shafts; #91576 & 91577 Fox Shock Bodies;   |

**Tires:**

|  |
|--|
| <b>Front Tires:</b> Pro-Line Electron (Sanded Slick) |
| <b>Front Compound:</b> S3                            |
| <b>Front Insert:</b> Pro-Line Closed Cell            |
| <b>Rear Tires:</b> Pro-Line Positron (Sanded Slick)  |
| <b>Rear Compound:</b> S3                             |
| <b>Rear Insert:</b> Pro-Line Closed Cell             |
| <b>Wheel (F/R):</b> Pro-Line 12mm Hex                |
| <b>Notes:</b> Liquid Wrench Penetrating Oil          |

**Chassis, Body, Wing:**

|   |
|---|
| <b>Body:</b> Pro-Line Axis  |
| <b>Front Wing:</b> #91866 B6.2  |
| <b>Rear Wing:</b> #91741 Team Associated B6.2 Kit   |
| <b>Wing Angle:</b> 0° <input type="checkbox"/> 3° <input checked="" type="checkbox"/> 6° <input type="checkbox"/> |
| <b>Chassis Length:</b> #91765 B6.2D Kit   |
| <b>Servo Weights:</b> #91745 FT Aluminum  |
| <b>Electronic Weights:</b> #91754 FT Graphite   |
| <b>Total Vehicle Weight:</b> 1575g  |