

**Front Suspension:**

Reset Forms

<b>Ride Height:</b>	14 mm
<b>Camber:</b>	-1.5 (Tierod Gap = 27.1 mm)
<b>Toe:</b>	+1 (Tierod Gap = 28.2 mm)
<b>Anti-Roll Bar:</b>	1.0 mm
<b>Arm Type:</b>	#91674 Gullwing, Hard
<b>Tower Type:</b>	#91768 Gullwing
<b>Caster Block Insert:</b>	+5
<b>Steering Block:</b>	4 mm
<b>Bulkhead Type:</b>	#91659 FT Brass Bulkhead
<b>Kick-Up Angle:</b>	25°
<b>Wheel Hex:</b>	#91683 FT Titanium Front Axles
<b>Notes:</b>	#91681 Caster Hat Bushings #91668 & #91669 FT Aluminum Steering Rack and Bellcranks

**Bump Steer Spacing:** 0.5 mm

**Steering Plate:** #91679 +0

**Steering Stop Spacing:** 0 mm

**Axle Height:** 1.5 mm

**Caster Block Spacing:** 1 mm

**Ball Stud Spacing:** 0 mm

**Ball Stud Spacing:** 0 mm

**Ball Stud Spacing:** 0 mm

**Rear Suspension:**

<b>Ride Height:</b>	14 mm
<b>Camber:</b>	-1.5 (Tierod Gap = 27.3 mm)
<b>Anti-Roll Bar:</b>	1.3 mm
<b>Arm Type:</b>	#91854 73mm, Hard
<b>Arm Spacing:</b>	Arm Forward
<b>Hub Spacing:</b>	Forward <input type="checkbox"/> Middle <input type="checkbox"/> Back <input checked="" type="checkbox"/>
<b>Shock Mounting Position:</b>	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
<b>Tower Type:</b>	#91769 Standard
<b>Wheel Hex:</b>	#91610 FT Clamping Hex, 7 mm
<b>CVA Bone Length:</b>	#91434 67 mm
<b>CVA Axle:</b>	#91859 +2 mm
<b>Notes:</b>	#92011 Arm Mount Inserts, 1*/0.5*

**C Mount:** Aluminum  Brass

**D Mount:** Aluminum  Brass

**Possible Insert Locations**

**Hub Insert:** +3  +2  +1  0

**Camber Link Spacing:** 2 mm

**Ball Stud Spacing:** 2 mm

**Ball Stud Spacing:** 4 mm

**Electronics:**


<b>Radio:</b> Sanwa M12s	<b>Servo:</b> #27109 Reedy RT1408 LP
<b>EPA: Throttle:</b> 100 %	<b>Brake:</b> 100 %
<b>ESC:</b> #27004 Reedy Blackbox 510R	
<b>ESC Settings:</b> See Setup Sheet	
<b>Motor:</b> #27402 Reedy S-Plus 17.5 (#27415 Reedy HT Rotor)	
<b>Wind:</b> 17.5	<b>Timing:</b> 47°
<b>Pinion:</b> #1349 FT 31T	<b>Spur:</b> 72
<b>Battery:</b> #27349 Reedy Zapper SG3 LP 4100mah	
<b>Battery Position:</b> 5F	
<b>Battery Weight:</b> #27304 Reedy Battery Weight, 22g	

**Drivetrain:**

<b>Transmission:</b>	<b>Laydown:</b> <input checked="" type="checkbox"/>
<b>3 Gear:</b> <input checked="" type="checkbox"/>	<b>Layback:</b> <input type="checkbox"/>
<b>4 Gear:</b> <input type="checkbox"/>	<b>Stand Up:</b> <input type="checkbox"/>
<b>Differential:</b>	<b>Ball Diff:</b> <input type="checkbox"/>
<b>Height:</b> 3	<b>Gear Diff:</b> <input checked="" type="checkbox"/>
<b>Gear Diff Mass:</b> N/A	
<b>Notes:</b> 10K/ 2 gear, #91784 Aluminum Cross Pin	

**Shocks:**

	Front	Rear
<b>Piston:</b>	#91626 2 x 1.6 Flat	#91627 2 x 1.7 Flat
<b>Fluid:</b>	#5433 FT 37.5wt	#5429 FT 35wt
<b>Spring:</b>	#91835 V2 Red	#91839 V2 Gray
<b>Int. Limiters:</b>	0	0
<b>Ext. Limiters:</b>	0	0
<b>Stroke:</b>	22 mm	28.5 mm
<b>Eyelet Length:</b>	Long	Long
<b>Cup Offset:</b>	+5 mm	+0 mm
<b>Notes:</b>	#91494 Machined Shock Spacers V2; #91493 FT X-Rings	



**Slipper Clutch:**

<b>Type:</b> #91802 & #91806 FT Vented Slipper Plates
<b># of Pads:</b> 2, LCF Pads

**Track Info:**

<b>Size:</b> Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input checked="" type="checkbox"/> Extra Large <input type="checkbox"/>
<b>Surface:</b> Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> Astroturf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
<b>Traction:</b> Low <input type="checkbox"/> Medium <input checked="" type="checkbox"/> High <input checked="" type="checkbox"/> Very High <input type="checkbox"/>
<b>Moisture:</b> Dry <input type="checkbox"/> Damp <input type="checkbox"/> Wet <input type="checkbox"/>
<b>Condition:</b> Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
<b>Temperature:</b> Ambient: 65° F Track:
<b>Notes:</b>
<b>Vehicle Comments:</b> #91727 FT Ti Turnbuckles, #91797 Ti Top Shaft Screw, #91653 Side Rails, Hard; #91616 & 91620 Chrome Shock Shafts; #91576 & 91577 Fox Shock Bodies; #1370 FT Aluminum Servo Horn, #92100 FT Aluminum Wng Buttons,

**Tires:**

<b>Front Tires:</b> JConcepts Swaggers
<b>Front Compound:</b> Pink
<b>Front Insert:</b> None
<b>Rear Tires:</b> JConcepts Twin Pins
<b>Rear Compound:</b> Pink
<b>Rear Insert:</b> JConcepts Open Cell (3/4 Width)
<b>Wheel (F/R):</b> #91757 & 9695 Team Associated 12mm Hex
<b>Notes:</b> #1597 FT Tire Adhesive

**Chassis, Body, Wing:**

<b>Body:</b> JConcepts S2
<b>Front Wing:</b> #91866 Team Associated B6.2
<b>Rear Wing:</b> #91741 Team Associated B6 (No Wicker Lip)
<b>Wing Angle:</b> 0° <input type="checkbox"/> 3° <input type="checkbox"/> 6° <input checked="" type="checkbox"/>
<b>Chassis Length:</b> #91850 B6.2 +3mm
<b>Servo Weights:</b> #91747 FT Steel
<b>Electronic Weights:</b> #91748 FT Steel
<b>Total Vehicle Weight:</b> 1502g