

Front Suspension:

| | |
|----------------------|--|
| Ride Height: | 20 mm |
| Camber: | -1 |
| Toe: | 0* (Tierod Gap = 27.2 mm) |
| Anti-Roll Bar: | None |
| Arm Type: | #91674 Gullwing, Hard |
| Tower Type: | #91768 Gullwing |
| Caster Block Insert: | 5* |
| Steering Block: | 4 mm |
| Bulkhead Type: | #91658 FT Aluminum |
| Kick-Up Angle: | 25* |
| Wheel Hex: | #91683 Titanium |
| Notes: | #1366 FT Aluminum Servo Horn, 25T #91667 Plastic Steering Rack & Bellcranks |

Bump Steer Spacing: 0 mm

Steering Plate: #91680 +1

Steering Stop Spacing: 0 mm

Axle Height: +2 mm

Caster Block Spacing: 1 mm

Ball Stud Spacing: 0 mm

Ball Stud Spacing: 1 mm

Ball Stud Spacing: 1 mm

Ball Stud Spacing: 2 mm

Ball Stud Spacing: 2 mm

Reset Forms

Rear Suspension:

| | |
|--------------------------|---|
| Ride Height: | 20 mm |
| Camber: | -1* |
| Anti-Roll Bar: | None |
| Arm Type: | #91853 73 mm, Standard |
| Arm Spacing: | Forward (2 mm Behind Arm) |
| Hub Spacing: | Forward <input type="checkbox"/> Middle <input checked="" type="checkbox"/> Back <input type="checkbox"/> |
| Shock Mounting Position: | Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/> |
| Tower Type: | #91769 Standard |
| Wheel Hex: | #71034 FT Clamping, 6.0 mm |
| CVA Bone Length: | #91434 67 mm |
| CVA Axle: | #91859 +2 mm |
| Notes: | |

C Mount: Aluminum Brass

D Mount: Aluminum Brass

Possible Insert Locations

Hub Insert: +3 +2 +1 0

Camber Link Spacing: 1 mm

Ball Stud Spacing: 2 mm

Ball Stud Spacing: 2 mm

Electronics:


| | | | |
|-------------------|-------------------------------------|---------|---------------|
| Radio: | Futaba 7PX | Servo: | Savox 1258-TG |
| EPA: Throttle: | 100 % | Brake: | 92 % |
| ESC: | Hobbywing XR10G2 Elite | | |
| ESC Settings: | See Baseline Setup Sheet | | |
| Motor: | Hobbywing G3 | | |
| Wind: | 7.5T | Timing: | 30* |
| Pinion: | 22 | Spur: | 78 |
| Battery: | ProTek 5800mAh | | |
| Battery Position: | 4.5F (Hole Slotted Between 4F & 5F) | | |
| Battery Weight: | #27304 Reedy 22g Under Battery | | |

Drivetrain:

| | | |
|-----------------|--|-------------------------------------|
| Transmission: | Laydown: <input checked="" type="checkbox"/> | |
| 3 Gear: | Layback: <input type="checkbox"/> | |
| 4 Gear: | Stand Up: <input type="checkbox"/> | |
| Differential: | Ball Diff: <input checked="" type="checkbox"/> | |
| Height: | 2 | Gear Diff: <input type="checkbox"/> |
| Gear Diff Mass: | | |
| Notes: | | |
| Slipper Clutch: | | |
| Type: | #91802 & #91806 FT Vented Slipper Hub | |
| # of Pads: | 2 x #91197 FT LCF | |

Shocks:

| | Front | Rear |
|----------------|---|-------------------------------|
| Piston: | 1x1.6+1x1.7 FT Flat Machined | #91627 2x1.7 FT Flat Machined |
| Fluid: | #5432 32.5 wt | #5422 30 wt |
| Spring: | #91329 V1 Gray | #91337 V1 White |
| Int. Limiters: | 0 | 0 |
| Ext. Limiters: | 0 | 0 |
| Stroke: | 23.0 mm | 29.0 mm |
| Eyelet Length: | Long | Long |
| Cup Offset: | 5 mm | 5 mm |
| Notes: | #91494 Machined Shock Spacers V2; #91493 FT X-Rings | |



Track Info:

| | | | |
|-----------------------|---|--------|-----|
| Size: | Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input checked="" type="checkbox"/> Extra Large <input type="checkbox"/> | | |
| Surface: | Dirt <input checked="" type="checkbox"/> Carpet <input type="checkbox"/> AstroTurf <input type="checkbox"/> Multi Surface <input type="checkbox"/> | | |
| Traction: | Low <input type="checkbox"/> Medium <input checked="" type="checkbox"/> High <input type="checkbox"/> Very High <input type="checkbox"/> | | |
| Moisture: | Dry <input checked="" type="checkbox"/> Damp <input type="checkbox"/> Wet <input type="checkbox"/> | | |
| Condition: | Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input checked="" type="checkbox"/> Hard Packed <input type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/> | | |
| Temperature: Ambient: | 65F | Track: | 65F |
| Notes: | | | |
| Vehicle Comments: | #91652 Side Rails, Standard; #91616 & 91620 Chrome Shock Shafts; #91576 & 91577 Fox Shock Bodies; | | |

Tires:

| | |
|-----------------|-----------------------------|
| Front Tires: | Pro-Line Electron (Spec) |
| Front Compound: | MC |
| Front Insert: | Pro-Line Closed Cell (Spec) |
| Rear Tires: | Pro-Line Positron (Spec) |
| Rear Compound: | MC |
| Rear Insert: | Pro-Line Closed Cell (Spec) |
| Wheel (F/R): | JConcepts Mono |
| Notes: | |

Chassis, Body, Wing:

| | |
|-----------------------|--|
| Body: | JConcepts F2 |
| Front Wing: | None |
| Rear Wing: | #91741 Team Associated B6.2 Kit |
| Wing Angle: | 0° <input type="checkbox"/> 3° <input type="checkbox"/> 6° <input checked="" type="checkbox"/> |
| Chassis Length: | #91765 Kit |
| Servo Weights: | None |
| Electronic Weights: | #91746 FT Aluminum |
| Total Vehicle Weight: | 1548g |