

## Front Suspension:

## Reset Forms

Ride Height:	15 mm
Camber:	-1°
Toe:	0° (Tierod Gap = 27.2 mm)
Anti-Roll Bar:	0.8 mm
Arm Type:	#91673 Gullwing, Standard
Tower Type:	#91880 B6.3, Gullwing
Wheel Hex:	#91682 5mm, Aluminum
Steering Block:	3 mm
Caster Block Insert:	2.5°
Bulkhead Type:	#91658 FT, Aluminum
Kick-Up Angle:	25°
Notes:	#91669 FT Aluminum Steering Rack

Bump Steer Spacing: 0 mm

Ball Stud Spacing: 0 mm

Steering Plate: #91902 FT HT +1

Steering Stop Spacing: 0 mm

Ball Stud Spacing: 1.5 mm

Caster Block Spacing: 1 mm

Ball Stud Spacing:

+3	<input type="checkbox"/>
+2	<input checked="" type="checkbox"/>
+1	<input type="checkbox"/>
0	<input type="checkbox"/>

## Rear Suspension:

Ride Height:	15 mm
Camber:	-1°
Anti-Roll Bar:	1.3 mm
Arm Type:	#91855 B6.2, Standard
Tower Type:	#91881 B6.3
Arm Spacing:	2 mm In Front Of Arm
Wheel Hex:	#91609 FT Clamping Hex, 5.0 mm
Shock Mounting Position:	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
Hub Spacing:	Fwd <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Back <input type="checkbox"/>
CVA Bone Length:	#91860 69 mm
CVA Axle Type:	#91859 +2 mm
Notes:	#91888 FT Rear Ballstud Mount, +2 mm; #91877 FT Rear Hubs, Blue Aluminum

C Mount: Aluminum  Brass

D Mount: Aluminum  Brass

Axle Height:

▼0	3▲	+3
▼1	2▲	+2
▲1	2▼	+1
▲0	3▼	+0

Camber Link Spacing: 2 mm

Ball Stud Spacing: 3 mm

Ball Stud Spacing: 4 mm

## Electronics:

Radio:	Sanwa M12S	Servo:	#27109 Reedy RT1408
EPA: Throttle:	100 %	Brake:	100 %
ESC:	#27004 Reedy Blackbox 510R		
ESC Settings:	See Setup Sheet		
Motor:	Reedy Sonic M4 + #27449 Reedy 540-M4 Mod Rotor (13.0x5.0x25.3)		
Wind:	7.0T	Timing:	30°
Pinion:	#1342FT 24T	Spur:	#92295 Octalock, 78T
Battery:	#27365 Reedy Zapper SG4 4100 mAh		
Battery Position:	5F		
Battery Weight:	#27304 Reedy LiPo Battery Weight Set 22g + 36g		

## Drivetrain:

Transmission:
Laydown: <input checked="" type="checkbox"/> Layback: <input type="checkbox"/>
Differential: Ball Diff: <input type="checkbox"/>
Height: <u>2</u> Gear Diff: <input checked="" type="checkbox"/>
Gear Diff Mass: N/A
Notes: #5454 FT 7k w/ 2 Planet Gears

## Slipper Clutch:

Type: #91802 & 91806 FT Vented Slipper Hub
# of Pads: 2 x #92285 FT Octalock LCF, 11mm
Setting: Front Tires Almost Lift Off The Ground

## Shocks:

	Front	Rear
Piston:	#91626 2 x 1.6 Flat	#91627 2 x 1.7 Flat
Fluid:	#5429 FT 35 wt	#5432 FT 32.5 wt
Spring:	#91834 Yellow V2	#91839 Gray V2
Limiters:	Int: 0 Ext: 0	Int: 0 Ext: 0
Stroke:	22.0 mm	28.0 mm
Eyelet Length:	Short (+0)	Extra Long (+4)
Cup Offset:	5 mm	0 mm
Notes:	#91494 Machined Shock Spacers V2 #91616 & 91620 FT Chrome Shock Shafts;	

## Track Info:

Size:	Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input type="checkbox"/> Extra Large <input checked="" type="checkbox"/>
Surface:	Dirt <input type="checkbox"/> Carpet <input type="checkbox"/> AstroTurf <input checked="" type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction:	Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input type="checkbox"/>
Moisture:	Dry <input type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
Condition:	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
Temperature:	Ambient: 65F Track: 65F
Notes:	Black Ozite Carpet

## Tires:

Front Tires:	JConcepts Swagger
Front Compound:	Pink
Front Insert:	None
Rear Tires:	JConcepts Nessi
Rear Compound:	Pink
Rear Insert:	JConcepts Open Cell (Narrowed 5mm)
Wheel (F/R):	#91757 & 9695 Team Associated 12mm Hex
Notes:	

## Body, Weight:

Body:	JConcepts S2
Front Wing:	#91866 B6.2
Rear Wing:	JConcepts Carpet Aero 6.5°
Wing Angle:	6°
Chassis Length:	#91893 B6.3 +3 mm
Servo Weights:	#91747 FT Steel
Electronic Weights:	#91748 FT Steel
Total Vehicle Weight:	1569g

Vehicle Comments: #91727 FT Titanium Turnbuckle Set; #91907 FT Laydown/Layback Motor Plate, 3.5 mm; #91797 FT Titanium Top Shaft Screw; #91870 FT Chassis Protective Sheet