

## Front Suspension:

## Reset Forms

Ride Height:	18.5 mm
Camber:	-1° (Tierod Gap = 22.6 mm)
Toe:	0° (Tierod Gap = 27.3 mm)
Anti-Roll Bar:	None
Arm Type:	#91674 Gullwing, Hard
Tower Type:	#91880 B6.3, Gullwing
Wheel Hex:	#91683 5mm, Titanium
Steering Block:	4 mm
Caster Block Insert:	0°
Bulkhead Type:	#91658 FT Aluminum
Kick-Up Angle:	25°
Notes:	#91668 FT Aluminum Bellcranks

Bump Steer Spacing:	0 mm
Ball Stud Spacing:	1 mm
Steering Plate:	#91902 FT HT +1
Steering Stop Spacing:	0 mm
Caster Block Spacing:	1 mm

**Ball Stud Spacing:**  
 +3   
 +2   
 +1   
 0

**Ball Stud Spacing:** 1 mm  
 B A  
 C B A

## Rear Suspension:

Ride Height:	18.5 mm
Camber:	-1° (Tierod Gap = 24.2)
Anti-Roll Bar:	None
Arm Type:	#91853 B6.2 73 mm, Standard
Tower Type:	#91881 B6.3
Arm Spacing:	1 mm Ahead & 1 mm Behind Arm
Wheel Hex:	#91609 FT Clamping Hex, 5.0 mm
Shock Mounting Position:	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
Hub Spacing:	Fwd <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Back <input type="checkbox"/>
CVA Bone Length:	#91860 69 mm
CVA Axle Type:	#91859 +2 mm
Notes:	#91889 FT Rear Ballstud Mount, +2 mm, Black; #91878 FT Rear Hubs, Black Aluminum

**C Mount:**  
 Aluminum  Brass

**D Mount:**  
 Aluminum  Brass

**Axle Height:**  
 ▼0 3 ▲ +3  
 ▼1 2 ▲ +2  
 ▲1 2 ▼ +1  
 ▲0 3 ▼ +0

**Camber Link Spacing:** 1 mm  
**Ball Stud Spacing:** 2 mm  
**Ball Stud Spacing:** 1 mm (w/ +2mm mount)

CBA

## Electronics:

Radio:	Sanwa M12S	Servo:	#27109 Reedy RT1408
EPA: Throttle:	100 %	Brake:	100 %
ESC:	#27004 Reedy Blackbox 510R		
ESC Settings:	See Setup Sheet		
Motor:	Reedy Sonic M4		
Wind:	7.5T	Timing:	20°
Pinion:	#1339FT 21T	Spur:	#92295 Octalock, 78T
Battery:	#27363 Reedy Zapper SG4 6300 mAh		
Battery Position:	5F		
Battery Weight:	#27304 Reedy LiPo Battery Weight Set 22g		

## Drivetrain:

Transmission:	Laydown: <input checked="" type="checkbox"/> Layback: <input type="checkbox"/>
Differential:	Ball Diff: <input checked="" type="checkbox"/>
Height:	2 Gear Diff: <input type="checkbox"/>
Gear Diff Mass:	N/A
Notes:	
Slipper Clutch:	Type: #91802 & 91806 FT Vented Slipper Hub
# of Pads:	2 x #92289 FT Octalock LCF, 19mm
Setting:	Front Tires Lift 30 mm

## Shocks:

	Front	Rear
Piston:	1x1.6+1x1.7 Thick Flat	#91627 2x 1.7 Thick Flat
Fluid:	#5432 FT 32.5 wt	#5422 FT 30 wt
Spring:	#91833 Blue V2	#91337 White V1
Limiters:	Int: 0 Ext: 0	Int: 0 Ext: 1
Stroke:	23.4 mm	29.0 mm
Eyelet Length:	Short (+0)	Long (+2)
Cup Offset:	5 mm	0 mm
Notes:	#91494 Machined Shock Spacers V2 #91616 & 91620 FT Chrome Shock Shafts;	

## Track Info:

Size:	Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input type="checkbox"/> Extra Large <input checked="" type="checkbox"/>
Surface:	Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> AstroTurf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction:	Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input checked="" type="checkbox"/>
Moisture:	Dry <input type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
Condition:	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
Temperature:	Ambient: 70F Track: 70F
Notes:	

## Tires:

Front Tires:	Proline Shadow (Sidewalls Glued)
Front Compound:	S3
Front Insert:	Proline 4wd Closed Cell
Rear Tires:	Proline Shadow
Rear Compound:	S3
Rear Insert:	Proline Closed Cell
Wheel (F/R):	Proline
Notes:	Liquid Wrench Penetrating Oil

## Body, Weight:

Body:	Proline Axis
Front Wing:	None
Rear Wing:	#91741 Team Associated B6 Kit
Wing Angle:	6°
Chassis Length:	#91893 B6.3 +3 mm
Servo Weights:	14g Behind Servo
Electronic Weights:	#91746 FT Aluminum
Total Vehicle Weight:	N/A

Vehicle Comments: #91727 FT Titanium Turnbuckle Set; #91987 FT Laydown/Layback Motor Plate, 3.5 mm, Black; #91797 FT Titanium Top Shaft Screw; #91870 FT Chassis Protective Sheet; FT Titanium Ballstuds