

## Front Suspension:

Reset Forms

Ride Height:	24 mm (Body Off)
Camber:	-1°
Toe:	0°
Anti-Roll Bar:	1.4 mm
Arm Type:	#71138 Gullwing, Standard
Tower Type:	#71136 Gullwing
Wheel Hex:	#71111 Front Axle, 8.5 mm
Steering Block:	4 mm
Caster Block Insert:	5°
Bulkhead Type:	#91658 FT Aluminum
Kick-Up Angle:	25°
Notes:	#91668 FT Aluminum Steering Bellcranks; #91469 Steering Link; #1369 FT Clamping Servo Horn, 15.5 mm

**Bump Steer Spacing:** 0.5 mm

**Ball Stud Spacing:** 1 mm

**Steering Plate:** #71144 +1

**Steering Stop Spacing:** 0 mm

**Ball Stud Spacing:** 2 mm

**Ball Stud Spacing:** 2 mm

**Caster Block Spacing:** 1 mm

**Axle Height:**  
 +3   
 +2   
 +1   
 0

## Rear Suspension:

Ride Height:	24 mm (Body Off)
Camber:	-1°
Anti-Roll Bar:	N/A
Arm Type:	#71140 Gullwing, Standard
Tower Type:	#71137 T6.2 Standard
Arm Spacing:	Rear (2 mm In Front Of Arm)
Wheel Hex:	#71014 FT Clamping Wheel Hex, 8.5 mm
Shock Mounting Position:	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
Hub Spacing:	Fwd <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Back <input type="checkbox"/>
Notes:	

**C Mount:**  
 Aluminum  Brass

**D Mount:**  
 Aluminum  Brass

**Axle Height:**  
 ▼0 3▲ +3  
 ▼1 2▲ +2  
 ▲1 2▼ +1  
 ▲0 3▼ +0

**Camber Link Spacing:** 2 mm

**Ball Stud Spacing:** 2 mm

**Ball Stud Spacing:** 2 mm

## Electronics:

Radio:	Sanwa M12S	Servo:	#27101 Reedy RT1508
EPA: Throttle:	100 %	Brake:	96 %
ESC:	#27004 Reedy Blackbox 510R		
ESC Settings:	See Setup Sheet		
Motor:	Reedy M3		
Wind:	#27442 7.0T	Timing:	28°
Pinion:	#1337 FT 19T	Spur:	78
Battery:	#27352 Reedy Zapper 6100 mAh 85C		
Battery Position:	5F		
Battery Weight:	#27304 Reedy LiPo Battery Weight Set - 36g		

## Drivetrain:


Transmission:	Laydown: <input checked="" type="checkbox"/>		
Stand Up:	Layback: <input type="checkbox"/>		
Differential:	Ball Diff: <input checked="" type="checkbox"/>		
Height:	+3	Gear Diff:	<input type="checkbox"/>
Gear Diff Mass:			
Notes:	3/4 Tire Rotation		

## Slipper Clutch:

Type:	#91802 & 91806 FT Vented Slipper Hubs
# of Pads:	2 x LCF
Setting:	Front Tires Pull Off The Ground 1"

## Shocks:

	Front	Rear
Piston:	1 x 1.6 + 1 x 1.7 mm	#91627 2 x 1.7 mm
Fluid:	#5433 FT 37.5 wt	#5422 FT 30 wt
Spring:	#91637 Gray	#91639 Green
Limiters:	Int: 2 Ext: 0	Int: 0 Ext: 0
Stroke:	27.9 mm	33.6 mm
Eyelet Length:	Long	Long
Cup Offset:	5 mm	0 mm
Notes:	#91494 Machined Shock Spacers; #91493 FT X-Rings; #91620 & 91624 FT Chrome Shock Shafts; #91577 & 91570 FT Fox Shock Bodies	



## Track Info:

Size:	Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input type="checkbox"/> Extra Large <input checked="" type="checkbox"/>
Surface:	Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> AstroTurf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction:	Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input checked="" type="checkbox"/>
Moisture:	Dry <input type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
Condition:	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input checked="" type="checkbox"/> Loamy <input type="checkbox"/>
Temperature:	Ambient: 85°F Track: 85°F
Notes:	
Vehicle Comments:	#71142 Side Rails, Standard

## Tires:

Front Tires:	Pro-Line Positrons (Slicks)
Front Compound:	S3
Front Insert:	Pro-Line Closed Cell
Rear Tires:	Pro-Line Positron (Slicks)
Rear Compound:	S3
Rear Insert:	Pro-Line Closed Cell
Wheel (F/R):	#7852 Team Associated 12mm Hex
Notes:	Liquid Wrench Penetrating Oil - Sit 10 Min

## Body, Weight:

Body:	#71126 T6.2 Kit
Spoiler:	#71126 T6.2 Kit
Servo Weights:	#1595 7g On Back Of Servo
Electronic Weights:	#91746 FT Aluminum
Total Vehicle Weight:	N/A
Notes:	