

Front Suspension:

Reset Forms

Ride Height:	25 mm (Body Off)
Camber:	-1°
Toe:	0° (Tierod Gap = 41.4 mm)
Anti-Roll Bar:	1.3 mm
Arm Type:	#71138 Gullwing, Standard
Tower Type:	#71136 Gullwing
Wheel Hex:	#71111 Front Axle, 8.5 mm
Steering Block:	4 mm
Caster Block Insert:	0°
Bulkhead Type:	#91658 FT Aluminum
Kick-Up Angle:	25°
Notes:	#91668 FT Aluminum Steering Bellcranks Bellcranks raised 3 mm with top plate ground for clearance #1369 FT Clamping Servo Horn, 15.5 mm

Bump Steer Spacing: 0 mm **Ball Stud Spacing:** 1 mm
Steering Plate: Schelle Type 1 **Steering Stop Spacing:** 1.0 mm
Ball Stud Spacing: 2 mm
Axle Height:
 +3
 +2
 +1
 0
Caster Block Spacing: 1 mm

Rear Suspension:

Ride Height:	25 mm (Body Off)
Camber:	-1°
Anti-Roll Bar:	N/A
Arm Type:	#71140 Gullwing, Standard
Tower Type:	#71137 T6.2 Standard
Arm Spacing:	Rear (2 mm In Front Of Arm)
Wheel Hex:	#71014 FT Clamping Wheel Hex, 8.5 mm
Shock Mounting Position:	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
Hub Spacing:	Fwd <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Back <input type="checkbox"/>
Notes:	Camber Link Hub Tower Reversed

C Mount: Aluminum Brass
D Mount: Aluminum Brass
Axle Height:
 ▼0 3▲ +3
 ▼1 2▲ +2
 ▲1 2▼ +1
 ▲0 3▼ +0
Camber Link Spacing: 0
Ball Stud Spacing: 2 mm
Ball Stud Spacing: 2 mm

Electronics:

Radio:	Futaba 7PXR	Servo:	Savox 1267
EPA: Throttle:	100 %	Brake:	92 %
ESC:	Hobbywing XR10 Pro		
ESC Settings:	See Baseline Setup Sheet		
Motor:	Hobbywing G3		
Wind:	6.5T	Timing:	30°
Pinion:	#1336 FT 18T	Spur:	#92296 81T Octalock
Battery:	ProTek 6100 mAh		
Battery Position:	5F		
Battery Weight:	#27304 Reedy LiPo Battery Weight Set - 22g		

Drivetrain:


Transmission:	Laydown: <input checked="" type="checkbox"/>
Stand Up:	Layback: <input type="checkbox"/>
Differential:	Ball Diff: <input checked="" type="checkbox"/>
Height:	+3 Gear Diff: <input type="checkbox"/>
Gear Diff Mass:	
Notes:	#6576 FT Precision Ground Diff Drive Rings

Slipper Clutch:

Type:	#91802 & 91806 FT Vented Slipper Hubs
# of Pads:	2 x #92286 FT Octalock LCF
Setting:	Front Tires Just Pull Off The Ground

Shocks:

	Front	Rear
Piston:	#91626 2 x 1.6 mm	#91627 2 x 1.7 mm
Fluid:	#5429 FT 35 wt	#5422 FT 30 wt
Spring:	#91638 Blue	#91640 White
Limiters:	Int: 0 Ext: 0	Int: 0 Ext: 0
Stroke:	28.5 mm	36.5 mm
Eyelet Length:	Long	Short
Cup Offset:	5 mm	5 mm
Notes:	#91494 Machined Shock Spacers; #91493 FT X-Rings; #91620 & 91624 FT Chrome Shock Shafts; #91577 & 91570 FT Fox Shock Bodies	



Track Info:

Size:	Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input type="checkbox"/> Extra Large <input checked="" type="checkbox"/>
Surface:	Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> AstroTurf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction:	Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input checked="" type="checkbox"/>
Moisture:	Dry <input type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
Condition:	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Bumpy <input checked="" type="checkbox"/> Grooved <input type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
Temperature:	Ambient: 45°F Track: 45°F
Notes:	
Vehicle Comments:	#71142 Side Rails, Standard

Tires:

Front Tires:	JConcepts Ellipse (Slicks)
Front Compound:	Silver
Front Insert:	JConcepts Closed Cell
Rear Tires:	JConcepts Ellipse (Slicks)
Rear Compound:	Silver
Rear Insert:	JConcepts Closed Cell
Wheel (F/R):	JConcepts Mono
Notes:	Foam Glued To Wheel: SXT Baja Blast - Burned In: Sit 20 min

Body, Weight:

Body:	JConcepts Finisher
Spoiler:	JConcepts Finisher
Servo Weights:	#91745 FT Aluminum
Electronic Weights:	#91746 FT Aluminum
Total Vehicle Weight:	N/A
Notes:	