

## Front Suspension:

Reset Forms

Ride Height:	24 mm (Body Off)
Camber:	-1°
Toe:	0° (Tierod Gap = 41.3 mm)
Anti-Roll Bar:	1.3 mm
Arm Type:	#71138 Gullwing, Standard
Tower Type:	#71136 Gullwing
Wheel Hex:	#71111 Front Axle, 8.5 mm
Steering Block:	4 mm
Caster Block Insert:	0°
Bulkhead Type:	#91659 FT Brass
Kick-Up Angle:	25°
Notes:	#91668 FT Aluminum Steering Bellcranks #1369 FT Clamping Servo Horn, 15.5 mm Bellcranks raised 3 mm with top plate ground for clearance

**Bump Steer Spacing:** 0 mm  
**Ball Stud Spacing:** 1 mm  
**Steering Plate:** #71144 Steering Arm Block, +1  
**Steering Stop Spacing:** 0  
**Ball Stud Spacing:** 1 mm  
**Ball Stud Spacing:** 1 mm  
**Caster Block Spacing:** 1 mm

**Axle Height:**  
 +3   
 +2   
 +1   
 0

## Rear Suspension:

Ride Height:	24 mm (Body Off)
Camber:	-1°
Anti-Roll Bar:	N/A
Arm Type:	#71140 Gullwing, Standard
Tower Type:	#71137 T6.2 Standard
Arm Spacing:	Rear (2 mm In Front Of Arm)
Wheel Hex:	#91610 FT Clamping Wheel Hex, 7.0 mm
Shock Mounting Position:	Front of Arm <input checked="" type="checkbox"/> Rear of Arm <input type="checkbox"/>
Hub Spacing:	Fwd <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Back <input type="checkbox"/>
Notes:	

**C Mount:**  
 Aluminum  Brass

**D Mount:**  
 Aluminum  Brass

**Axle Height:**  
 ▼0 3▲ +3  
 ▼1 2▲ +2  
 ▲1 2▼ +1  
 ▲0 3▼ +0

**Camber Link Spacing:** 3 mm  
**Ball Stud Spacing:** 1 mm  
**Ball Stud Spacing:** 3 mm

## Electronics:

Radio:	Sanwa M17	Servo:	#27101 Reedy RT1508
EPA: Throttle:	100 %	Brake:	90 %
ESC:	#27004 Reedy Blackbox 510R		
ESC Settings:	See Setup Sheet		
Motor:	Reedy M4		
Wind:	#27441 7.5T	Timing:	24°
Pinion:	#1338 FT 20T	Spur:	#92296 81T Octalock
Battery:	#27352 Reedy Zapper 6100 mAh 85C		
Battery Position:	4F		
Battery Weight:	N/A		

## Drivetrain:


Transmission:	Laydown: <input checked="" type="checkbox"/>
Stand Up:	Layback: <input type="checkbox"/>
Differential:	Ball Diff: <input checked="" type="checkbox"/>
Height:	Gear Diff: <input type="checkbox"/>
Gear Diff Mass:	
Notes:	#6576 FT Precision Ground Diff Drive Rings

## Slipper Clutch:

Type:	#91802 & 91806 FT Vented Slipper Hubs
# of Pads:	2 x #92286 FT Octalock LCF
Setting:	Front Tires Just Pull Off The Ground

## Shocks:

	Front	Rear
Piston:	#91626 2 x 1.6 mm	#91627 2 x 1.7 mm
Fluid:	#5429 FT 35 wt	#5422 FT 30 wt
Spring:	#91636 White	#91640 White
Limiters:	Int: 1 Ext: 0	Int: 1 Ext: 0
Stroke:	27.0 mm	34 mm
Eyelet Length:	Long	Long
Cup Offset:	5 mm	0 mm
Notes:	#91494 Machined Shock Spacers; #91493 FT X-Rings; #91620 & 91624 FT Chrome Shock Shafts; #91577 & 91570 FT Fox Shock Bodies	



## Track Info:

Size:	Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input checked="" type="checkbox"/> Extra Large <input type="checkbox"/>
Surface:	Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> AstroTurf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction:	Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input type="checkbox"/> Very High <input checked="" type="checkbox"/>
Moisture:	Dry <input type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
Condition:	Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
Temperature:	Ambient: 50°F Track: 50°F
Notes:	
Vehicle Comments:	#71142 Side Rails, Standard

## Tires:

Front Tires:	JConcepts Ellipse (Slicks)
Front Compound:	Silver
Front Insert:	JConcepts Dirt Tech
Rear Tires:	JConcepts Ellipse (Slicks)
Rear Compound:	Silver
Rear Insert:	JConcepts Dirt Tech
Wheel (F/R):	JConcepts Mono
Notes:	N/A

## Body, Weight:

Body:	JConcepts Finisher
Spoiler:	JConcepts Finisher
Servo Weights:	#91764 FT Carbon Fiber
Electronic Weights:	#91754 FT Carbon Fiber
Total Vehicle Weight:	N/A
Notes:	