RC12	Diffrere			.Dales			
	Treds	tadle		_ Evenile			
FACTORY TEAM	Qualifys	<i>1</i> 02 🗆	Mcfins	_ ####################################	Best Lap ti	îlmes	
Track Info:							
Size: Small Medium Large X-Large		Position:					
Surface: Carpet Asphalt Indoor Outdoor							
Traction: Low Medium High Wet	11 248		OL,		To O		
Condition: Bumpy Smooth	 			<u>†</u>		<u>†</u>	
Temperature: AmbientTrack	Droop:	Ride Height:	Ride He	ight:	Droop:	ide Height:	
Vehicle Info:	Caster:	Caster S	hims: Shim:		Track Width Inserts	: Front Wheelbase:	
Body:	0mm 2°	1 1	2°		Composite	Std	
Weight:	0.55mm 4°	1 1 1	_ 5mm)		Aluminum	40	
Notes:	1.10mm 6°		4°		Omm 🔲 🔾		
Shocke	1.65mm 8°		0mm) 🔾 🗀		+0.5mm	0	
Piston:	Dynamic Strut			00	+1.5mm		
Fluid:	0°	OFOE			+2mm	+2mm	
Spring:	5	1000		ı			
Rebound:	7.5°						
Pre Load:	10° 🔲 🔾	_				•	
Free Length:	Shim:	<u>-</u> L		Shim:		. 0 -	
Notes:	11====		27. 1	Snim:		ŬΙ	
Diff Setting:	Shim:		Shim:			Camber:	
	Shim:					Right:	
Loose Medium Tight	Spring:					Left:	
Electronics:	Kingpin Fluid:				- 19		
Radio:	Shim:	3					
Servo:				, ,			
EPA: Throttle: % Brake: %		Side Spring:	Axle	1.0 0.75 0.5	0.25 0 0.25 0.5	0.75 1.0 STD + 1 mn	
ESC:	Pre Load	Pre Load:	Height	$\Box \Box \Box$			
ESC Settings:	ll lie Loud			<u> </u>			
Motor:		Spring:	Shim:			Shim:	
Timing:	Free 🛣			The v	3		
Pinion: Spur:	Length T	Damper Tube:					
Rollout:							
Battery:		Fluid:	Shim	:		Shim:	
Notes:		Vidth:	Axle Shim:		Axle Shim:	Width:	
Tires:	1 -						
Front Tires:	11						
Front Tire Dia:	ill						
Rear Tire:	ill		y				
Rear Tire Dia:	i ll	6					
Notes:	i ll				D OTT		
Front Tire Left Right	'), E		
Additive: Additive Time:						111111111111111111111111111111111111111	
Rear Tire Additive: Additive Time:	Toe:		Servo Posit Right: Left:	ion: Battery Inline: Transve	erse:		
				Fwd			
# For more setups, visit RC10.com and click on "Setup Sheets"							