

Setup Sheet for Team Associated's RC8

Rev. 2

:: Front Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

kickup bushing
 # 2 UP/ 1 REAR
 up down

steering rack:
 back
 mid
 front

hinge pin bushing
 # 2
 up down

camber: -2 °
 caster: 16 °
 toe: 0 °
 ride height: 30 mm

:: Rear Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

anti-squat bushing
 # 3
 up down

wheelbase:
 long
 medium
 short

camber: -2 °
 toe: 3 °
 ride height: 30 mm

:: Front Shocks

spring: XRAY LITE BLUE piston: 1.6
 shock fluid: 55 length: _____

:: Rear Shocks

spring: XRAY LITE BLUE piston: 1.6
 shock fluid: 50 length: _____

:: Differentials

front fluid: 5K
 center fluid: 5K
 rear fluid: 5K

:: Wing

location: forward back
 angle: low med. high
 type: _____

:: Notes

:: Engine

engine: RB WS7 3 restrictor: STD
 muffler: AE FT temp: _____
 glow plug: 6
 fuel: BYRON GEN2

:: Gearing/Clutch

gearing: 16/44
 clutch shoes: 2 CARBON 1 ALLOY
 clutch spring: .9mm 1.0mm 1.1mm
 other: _____

:: Front Tires

tire: PROLINE
 compound: M3 HOT M2 COLD
 insert: STD
 wheel: AE

:: Rear Tires

tire: _____
 compound: _____
 insert: _____
 wheel: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq:
 comments: RT ARM MOUNTS, RTR BRACES. TESTED
NEW 3 CHAMBER RB PIPE FOR EURO S.
WORKED VERY WELL. No 3001RB

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____