

Front Suspension:

Ride Height: 27 mm
Camber: -1*
Toe: +3* (Tierod Gap = 22.0 mm)
Anti-Roll Bar
Size: 2.3 mm (Black)
Gap: 2 mm
Ackerman
Notes: #81063 FT Steering Block Arm +2 Deg, Aluminum
Drive Shaft: CVAs: <input checked="" type="checkbox"/> Universals: <input type="checkbox"/>
Chassis Brace: Short: <input checked="" type="checkbox"/> Long: <input type="checkbox"/>
Hex: #81079 Wheel Hex, +1 mm
Notes: #81028 FT Carbon Fiber Shock Tower #81085 FT Servo Saver Arm, Aluminum

Caster Shim: 2.0 mm F / 2.0 mm R
Upper Ball Type: #81068 Aluminum
Upper Ball Shim: 0
Washers: 0
Lower Ball Shim: 0

Wheelbase Shim: 0 mm F / 1 mm R
Lower Ball Type: #81068 Aluminum
Upper Arm Mount:
Arm Mount A:
Arm Mount B:

Rear Suspension:

Ride Height: 27 mm
Camber: -3* (Tierod Gap = 16.0 mm)
Anti-Roll Bar
Size: 2.5 mm (White)
Gap: 0 mm (Ball Reversed)
Drive Shaft: CVAs: <input checked="" type="checkbox"/> Universals: <input type="checkbox"/>
Chassis Brace: Short: <input checked="" type="checkbox"/> Long: <input type="checkbox"/>
Hex: #81079 Wheel Hex, +1 mm
Notes: #81029 FT Carbon Fiber Shock Tower

Hub Shim: 2.5 mm F / 2.5 mm R	Wheelbase Shim: 1 mm F / 0 mm R
Arm Mount C:	Arm Mount D:

Electronics and Engine:

Radio: Sanwa M12S
Receiver Battery: #304 Reedy 1600 mAh
Throttle Servo: #27107 Reedy RT2207A
Steering Servo: #27107 Reedy RT2207A
EPA: Throttle: 54 % Brake: 53 (Fuel Tubing) %
Brake Bias: 50% F / 50% R D/R: 100 %
Engine: Mx B2102 Temp: 240F
Muffler: O.S. 2090 Fuel: Mx 25%
Restrictor: 6.0 mm Glow Plug: O.S. P3
Notes: #1363 FT Aluminum Servo Horn, 18.5mm

Differential:

	Fluid:	Gear Set:	Planet O-Rings:
Front:	5,000	HTC	0
Center:	7,000	HTC	0
Rear:	3,000	HTC	0

Clutch and Gearing:

Spur Gear: 46	Bell: 13
Shoes: 2 x #81402 Composite + 2 x #81375 Aluminum	
Springs: 2 x 0.95 (Green) + 2 x 1.00 (Gold)	
Notes: RC8B3.1 4-Shoe Clutch	

Shocks:

	Front	Rear
Piston:	8 x 1.2 Tapered	8 x 1.3 Tapered
Fluid:	50 wt	50 wt
Cap:	#81179 Bleeder	#81179 Bleeder
Rebound:	10 mm	10 mm
Spring:	White V2	White V2
Free Length:	104 mm	120.5 mm
Notes:	#81174 & #81177 FT Chrome Shock Shafts; #81164 & #81165 Fox Shock Bodies; #81407 FT Shock Seal Bushing	
Set		



Track Info:

Size: Small <input type="checkbox"/> Medium <input checked="" type="checkbox"/> Large <input type="checkbox"/> Extra Large <input type="checkbox"/>
Surface: Dirt <input type="checkbox"/> Carpet <input checked="" type="checkbox"/> Astroturf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction: Low <input type="checkbox"/> Medium <input type="checkbox"/> High <input checked="" type="checkbox"/> Very High <input type="checkbox"/>
Moisture: Dry <input checked="" type="checkbox"/> Damp <input type="checkbox"/> Wet <input type="checkbox"/>
Condition: Indoor <input type="checkbox"/> Outdoor <input checked="" type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input type="checkbox"/> Bumpy <input checked="" type="checkbox"/> Grooved <input type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
Temperature: Ambient: 70F Track: 70F
Notes: Track broke apart and had some dirt clods and rocks

Tires:

Front Tires: JConcepts Stalker
Front Compound: O2
Front Insert: JConcepts Dirt Tech
Rear Tires: JConcepts Stalker
Rear Compound: O2
Rear Insert: JConcepts Dirt Tech
Wheel (F/R): JConcepts Mono (Stiff Flex)
Notes:

Body, Wings:

Body: JConcepts S3 (Lightweight)
Wing: #81108 Team Associated Kit / JConcepts Front Nose Scoop
Wing Height: High: <input checked="" type="checkbox"/> Low: <input type="checkbox"/>
Gap to Tower: Stock Location
Weight:
Total Vehicle Weight: ~3350g
Notes: No weight added to the chassis.

Vehicle Comments:

Notes: #81274 Upper Titanium Screw Kit; Kit engine mount