

Front Suspension:

Ride Height: 23mm (Body On + 3/4 Tank)

Toe: Tierod Gap = 23.0 mm **Hex:** #81081 +0

Anti-Roll Bar

Size: 2.2 mm

Gap: 1.5 mm

Ackerman

Steering Arm Plate: #81063 +2 (Kit)

Drive Shaft: CVAs: Universals:

Chassis Brace: Short: Long:

Notes: #81085 Servo Saver Arm, Aluminum

Caster Shim: 1 mm

Insert Type: Plastic

Upper Ball Type: #81068 Aluminum

Upper Ball Shim: 1.4 mm

Washers: None

Lower Ball Shim: 0 mm

Wheelbase Shim: 1 mm (Arm Forward)

Insert Type: Plastic

Lower Ball Type: #81067 Steel

Upper Arm Mount:

Arm Mount A:

Arm Mount B:

Rear Suspension:

Ride Height: 29 mm (Body On + 3/4 Tank)

Camber: Tierod Gap = 16.4 mm **Hex:** #81081 +0

Anti-Roll Bar

Size: 2.8 mm

Gap: 2 mm

Drive Shaft: CVAs: Universals:

Chassis Brace: Short: Long:

Notes: Rear Shock Standoffs Shimmed Back 5 mm

Hub Shim: Meidum Back / Thick + Thin Front

Wheelbase Shim: 1 mm (Arm Back)

Arm Mount C:

Arm Mount D:

Insert Type: Plastic

Electronics and Engine:

Radio: Sanwa ZZ

Receiver Battery: #27313 Reedy LiPo Pro 2400 mAh 7.4v

Throttle Servo: Reedy

Steering Servo: Reedy

EPA: Throttle: 55 % Brake: 65 %

Brake Bias: 50%F / 50%R **D/R:** 100% %

Engine: REDS Gen 2 **Temp:** 101c

Muffler: S 2143 **Fuel:** XTR Shoot 25%

Restrictor: 7.5 mm **Glow Plug:** TS3

Notes:

Differential:

| | Front | Center | Rear |
|-----------------|-------------|--------------|-------------|
| Fluid: | #5454 FT 7k | #5455 FT 10k | #5452 FT 3k |
| Gears: | HTC | HTC | HTC |
| Mass: | N/A | N/A | N/A |
| O-Rings: | No | No | No |

Clutch and Gearing:

Spur Gear: 46 **Bell:** 13


Shoes: Aluminum x3

Springs: 1.0 mm x 3

Notes: #81002 & 81003 43/13 Ring/Pinion Gearing

Shocks:

| | Front | Rear |
|-----------------|---|------------------------------|
| Piston: | #81210 8x1.2 Tapered, Angled | #81211 8x1.3 Tapered, Angled |
| Fluid: | #5434 FT 42.5 wt | #5430 FT 45 wt |
| Bladder: | #81453 Stiff | #81453 Stiff |
| Rebound: | None | None |
| Spring: | 9.25T / 70 mm | 10.75T / 83 mm |
| Length: | 105 mm | 121 mm |
| Notes: | #81174 & #81177 Chrome Shock Shafts; #81407 Machined Shock Internals; | |



Track Info:

Size: Small Medium Large Extra Large

Surface: Dirt Carpet Astroturf Multi Surface

Traction: Low Medium High Very High

Moisture: Dry Damp Wet

Condition: Indoor Outdoor Dusty Hard Packed
 Bumpy Grooved Smooth Loamy

Temperature: Ambient: 26°C Track: N/A

Notes:

Tires:

Front Tire/Compound/Insert/Wheel:
 Pro-Line Fugitive / S4 / Pro-Line Closed Cell / Pro-Line Hard

Rear Tire/Compound/Insert/Wheel:
 Pro-Line Fugitive / S4 / Pro-Line Closed Cell / Pro-Line Hard

Notes:

Radio Tray Flex Assembly:

Transponder Mount: **None:**

Radio Tray Brace:

Body and Wing:

Body: Bittydesign Vision

Wings: #81104 Team Associated IFMAR Kit

Wing Height: High: Low:

Gap to Tower: 20 mm

Weight:

Total Weight: 3565g

Notes:

Vehicle Comments:

Notes: #81048 FT Aluminum Tumbuckle Ball Set; T-Works Titanium Screws & Tumbuckles