

RESET

Front Suspension:

Ride Height: 27 mm
Camber: -1
Toe: +2
Anti-Roll Bar
Size: 2.4 mm
Gap: 4 mm
Ackerman
1 2 3 4 5
Notes: Servo saver gap 2mm; #81301 Short chassis brace;

Caster Shim: 2 mm
Upper Ball Type: Aluminum
Upper Ball Shim: 1.5 mm
Lower Ball Shim: 0 mm

Wheelbase Shim: 1 mm
Lower Ball Type: Aluminum
Upper Arm Mount:
Arm Mount A:
Arm Mount B:

Rear Suspension:

Ride Height: 28 mm
Camber: -2
Anti-Roll Bar
Size: 2.7 mm
Gap: 0 mm
Notes: #81059 Mud flaps #81301 Short chassis brace

Hub Shim: Middle
Arm Mount C:
Arm Mount D:
Wheelbase Shim: 1 mm

Electronics and Engine:

Radio: Futaba 4PK
Receiver Battery: Reedy #304 1800 mAh
Throttle Servo: Futaba 9352HV
Steering Servo: Futaba 9252HV
EPA: Throttle: 68 % Brake: 35 %
Brake Bias: F40/R60 D/R: 100 %
Engine: O.S. B2101 Temp: N/A
Muffler: OS 2090 Fuel: VP 30%
Restrictor: 6.0 mm Glow Plug: P3

Differential Fluid:


Front: 15,000 AE
Center: 15,000 AE
Rear: 10,000 AE
Notes: 2 shims behind each planet gear & no gasket

Clutch and Gearing:

Spur Gear: 46	Bell: 13
Shoes: 3 x #89134 Soft Aluminum	
Springs: 3 x 1.0	
Notes: AE Clutch	

Shocks:

	Front	Rear
Piston:	6 x 1.3 Flat Kit	6 x 1.3 Tapered Kit
Fluid:	35 wt. AE	35 wt. AE
Spring:	Blue	White
Stroke:	N/A	N/A
Free Length:	105 mm	125.5 mm
Notes:	Rear shock eyelets unscrewed 2 mm and droop screw pocket recessed	



Track Info:

Size: Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input checked="" type="checkbox"/> Extra Large <input type="checkbox"/>
Surface: Dirt <input checked="" type="checkbox"/> Carpet <input type="checkbox"/> Astroturf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
Traction: Low <input type="checkbox"/> Medium <input checked="" type="checkbox"/> High <input type="checkbox"/> Very High <input type="checkbox"/>
Moisture: Dry <input checked="" type="checkbox"/> Damp <input type="checkbox"/> Wet <input type="checkbox"/>
Condition: Indoor <input type="checkbox"/> Outdoor <input checked="" type="checkbox"/> Dusty <input checked="" type="checkbox"/> Hard Packed <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> Grooved <input checked="" type="checkbox"/> Smooth <input checked="" type="checkbox"/> Loamy <input type="checkbox"/>
Temperature: Ambient: 100 Track: 115
Notes:

Tires:

Front Tires: Pro-Line Fugitive
Front Compound: X1
Front Insert: Pro-Line Closed Cell
Rear Tires: Pro-Line Fugitive
Rear Compound: X1
Rear Insert: Pro-Line Closed Cell
Wheel (F/R): Pro-Line
Notes:

Body, Wings:

Body: Team Associated Kit
Wing: Pro-Line Lexan
Wing Height: High: <input type="checkbox"/> Low: <input checked="" type="checkbox"/>
Gap to Tower: 19 mm to rear of tower
Weight:
Total Vehicle Weight: 3300g
Notes:

Vehicle Comments:

Notes: Team Associated Titanium Screw Kit #81274; Racers Edge aluminum steering servo horn; Steering Speed Turn 85% & Return 100%;