

**RESET**

## Front Suspension:

<b>Ride Height:</b> 25 mm
<b>Camber:</b> -2°
<b>Toe:</b> +2°
<b>Anti-Roll Bar</b>
<b>Size:</b> 2.4 mm (Green)
<b>Gap:</b> 2 mm
<b>Ackerman</b>
<b>Notes:</b> #81066Kit Ackerman Plates
1 2 3 4 5
<b>Drive Shaft:</b> CVAs: <input checked="" type="checkbox"/> Universals: <input type="checkbox"/>
<b>Chassis Brace:</b> Short: <input checked="" type="checkbox"/> Long: <input type="checkbox"/>
<b>Hex:</b> #81079 +1 Hex
<b>Notes:</b> #81291 Arm Mount, A HRC; #81026 Aluminum Front Shock Tower; Updated Front A-Arm

<b>Caster Shim:</b> 3 mm F / 1 mm R
<b>Upper Ball Type:</b> #81068 Aluminum
<b>Upper Ball Shim:</b> 0.7 mm
<b>Washers:</b> 0 mm
<b>Lower Ball Shim:</b> 1 mm

<b>Wheelbase Shim:</b> 1 mm R
<b>Lower Ball Type:</b> #81068 Aluminum
<b>Upper Arm Mount:</b>
<b>Arm Mount A:</b>
<b>Arm Mount B:</b>

## Rear Suspension:

<b>Ride Height:</b> 27 mm
<b>Camber:</b> -1.5°
<b>Anti-Roll Bar</b>
<b>Size:</b> 2.6 mm (Gray)
<b>Gap:</b> 0 mm
<b>Drive Shaft:</b> CVAs: <input checked="" type="checkbox"/> Universals: <input type="checkbox"/>
<b>Chassis Brace:</b> Short: <input checked="" type="checkbox"/> Long: <input type="checkbox"/>
<b>Hex:</b> #81079 +1 Hex
<b>Notes:</b> #81027 Aluminum Rear Shock Tower; #81075 Plastic Rear Hubs; Updated Rear A-Arm

<b>Hub Shim:</b> 2.5 mm F / 2.5 mm R
<b>Wheelbase Shim:</b> 1 mm R

<b>Arm Mount C:</b>
<b>Arm Mount D:</b>

## Electronics and Engine:

<b>Radio:</b> Sanwa M12S
<b>Receiver Battery:</b> #304 Reedy 1600 mAh
<b>Throttle Servo:</b> #27106 Reedy RS1806A Digital HV High-Speed
<b>Steering Servo:</b> #27107 Reedy RS2207A Digital HV Hi-Torque
<b>EPA:</b> Throttle: 36 % Brake: 79 %
<b>Brake Bias:</b> 50 / 50 <b>D/R:</b> 100 %
<b>Engine:</b> LRP ZZ.21c <b>Temp:</b> 240°
<b>Muffler:</b> O.S. 2090 <b>Fuel:</b> VP Powermaster 30%
<b>Restrictor:</b> 6 mm <b>Glow Plug:</b> O.S. P4

## Differential Fluid:


<b>Front:</b> 7,000
<b>Center:</b> 7,000
<b>Rear:</b> 4,000
<b>Notes:</b> V2 Diffs

## Clutch and Gearing:

<b>Spur Gear:</b> 46 <b>Bell:</b> 13
<b>Shoes:</b> 2 Aluminum / 2 Carbon
<b>Springs:</b> N/A
<b>Notes:</b> 4 Shoe Clutch; Steel Flywheel

## Shocks:

	Front	Rear
<b>Piston:</b>	6 x 1.3 Flat	6 x 1.3 Flat
<b>Fluid:</b>	35 wt	30 wt
<b>Cap:</b>	#81179 Bleeder	#81179 Bleeder
<b>Rebound:</b>	0	0
<b>Spring:</b>	70/9.0T	86/10.5T
<b>Free Length:</b>	105 mm	120 mm
<b>Notes:</b> #81164 & #81165 Kashima Shock Bodies; #81170 & #81171 Gold Shock Shafts; Drilled Mugen Blank Pistons		



## Track Info:

<b>Size:</b> Small <input type="checkbox"/> Medium <input type="checkbox"/> Large <input checked="" type="checkbox"/> Extra Large <input type="checkbox"/>
<b>Surface:</b> Dirt <input checked="" type="checkbox"/> Carpet <input type="checkbox"/> Astroturf <input type="checkbox"/> Multi Surface <input type="checkbox"/>
<b>Traction:</b> Low <input type="checkbox"/> Medium <input checked="" type="checkbox"/> High <input type="checkbox"/> Very High <input type="checkbox"/>
<b>Moisture:</b> Dry <input checked="" type="checkbox"/> Damp <input checked="" type="checkbox"/> Wet <input type="checkbox"/>
<b>Condition:</b> Indoor <input type="checkbox"/> Outdoor <input checked="" type="checkbox"/> Dusty <input type="checkbox"/> Hard Packed <input type="checkbox"/> Bumpy <input checked="" type="checkbox"/> Grooved <input type="checkbox"/> Smooth <input type="checkbox"/> Loamy <input type="checkbox"/>
<b>Temperature:</b> Ambient: 50F Track: 50F
<b>Notes:</b> High speed & rough through jump sections

## Tires:

<b>Front Tires:</b> Pro-Line Electroshot
<b>Front Compound:</b> X3
<b>Front Insert:</b> Pro-Line Blue Closed Cell
<b>Rear Tires:</b> Pro-Line Holeshot
<b>Rear Compound:</b> X3
<b>Rear Insert:</b> Pro-Line Blue Closed Cell
<b>Wheel (F/R):</b> Pro-Line
<b>Notes:</b>

## Body, Wings:

<b>Body:</b> #81110 Team Associated Kit
<b>Wings:</b> #81106 Team Associated Kit
<b>Wing Height:</b> High: <input type="checkbox"/> Low: <input checked="" type="checkbox"/>
<b>Gap to Tower:</b> 26 mm
<b>Weight:</b>
<b>Total Vehicle Weight:</b> 3425g
<b>Notes:</b>

## Vehicle Comments:

<b>Notes:</b> #1363 FT Aluminum Servo Horn, 18.5 mm; #81184 Bleeder Shock Cap Seals; #81221 Spring Collars, 20 mm; #81194 Shock Rod End & Spring Cups, 20mm
---