


## :: Front Suspension

anti-roll bar:

2.2 - black  
 2.5 - silver  
 2.8 - gold

hinge pin bushing  
 # \_\_\_\_\_  
 up  down

bump-steer washers:  
 in \_\_\_\_\_ out \_\_\_\_\_



camber: \_\_\_\_\_

caster: \_\_\_\_\_

toe: \_\_\_\_\_

kickup bushing  
 # \_\_\_\_\_  
 up  down

ride height: \_\_\_\_\_

## :: Rear Suspension

anti-roll bar:

2.2 - black  
 2.5 - silver  
 2.8 - gold

wheelbase:

long  
 medium  
 short

camber: \_\_\_\_\_

toe: \_\_\_\_\_

hub:  
upper \_\_\_\_\_  
lower \_\_\_\_\_

anti-squat bushing  
 # \_\_\_\_\_  
 up  down

ride height: \_\_\_\_\_

## :: Front Shocks

spring: \_\_\_\_\_ piston: \_\_\_\_\_

shock fluid: \_\_\_\_\_ length: \_\_\_\_\_

shock cap: \_\_\_\_\_

## :: Rear Shocks

spring: \_\_\_\_\_ piston: \_\_\_\_\_

shock fluid: \_\_\_\_\_ length: \_\_\_\_\_

shock cap: \_\_\_\_\_

## :: Differentials

front fluid: \_\_\_\_\_

center fluid: \_\_\_\_\_

rear fluid: \_\_\_\_\_

## :: Wing

location:  forward  back

angle:  low  med.  high

type: \_\_\_\_\_

## :: Chassis Braces / Wheel Hex

chassis braces:

standard  molded  aluminum

wheel hex:

standard  narrow

## :: Electronics

motor & wind: \_\_\_\_\_

esc: \_\_\_\_\_ setting: \_\_\_\_\_

batteries: \_\_\_\_\_

radio: \_\_\_\_\_

steering expo: \_\_\_\_\_

brake e.p.a. : \_\_\_\_\_

throttle expo: \_\_\_\_\_

servo: \_\_\_\_\_

initial brake: \_\_\_\_\_ drag brake: \_\_\_\_\_

## :: Gearing

pinion gear: \_\_\_\_\_

spur gear: \_\_\_\_\_

## :: Tires

tire (F/R): \_\_\_\_\_ / \_\_\_\_\_

compound (F/R): \_\_\_\_\_ / \_\_\_\_\_

insert: \_\_\_\_\_ wheel: \_\_\_\_\_

traction additive: \_\_\_\_\_

## :: Race and Vehicle Comments

qualify: \_\_\_\_\_ main: \_\_\_\_\_ finish: \_\_\_\_\_ tq:

comments: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

## :: Track Info

smooth:  bumpy:  blue groove:

traction:  high  med.  low

soft dirt:  grass:  clay:  wet:

dusty:  other: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_