

:: Front Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

hinge pin bushing
 # 2
 up down

bump-steer washers:
 in _____ out _____

camber: -2 °
 caster: 16 °
 toe: 0 °

kickup bushing
 # 2
 up down

ride height: 27mm

:: Rear Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

wheelbase:
 long
 medium
 short

camber: -2 °
 toe: 3 °

hub:
 upper _____
 lower _____

anti-squat bushing
 # 2
 up down

ride height: 27mm

:: Front Shocks

spring: (4.7 lb) Bronze piston: 1.3
 shock fluid: 25 wt length: 113mm
 shock cap: aluminum

:: Rear Shocks

spring: (3.3 lb) Silver piston: 1.3
 shock fluid: 25 wt length: 125mm
 shock cap: aluminum

:: Differentials

front fluid: 5000cst
 center fluid: 5000cst
 rear fluid: 5000cst

:: Wing

location: forward back
 angle: low med. high
 type: _____

:: Chassis Braces / Wheel Hex

chassis braces:
 pivot molded aluminum
 wheel hex:
 standard narrow

:: Electronics

motor & wind: _____
 esc: _____ setting: _____
 batteries: _____
 radio: _____
 steering expo: _____
 brake e.p.a. : _____
 throttle expo: _____
 servo: _____
 initial brake: _____ drag brake: _____

:: Gearing

pinion gear: 15t
 spur gear: 46t

:: Tires

tire (F/R): _____ / _____
 compound (F/R): _____ / _____
 insert: _____ wheel: _____
 traction additive: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq:
 comments: _____

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____

