

:: Front Suspension

anti-roll bar:

2.2 - black
 2.5 - silver
 2.8 - gold

hinge pin bushing
2F/1R
 up down

bump-steer washers:
 in 1 out
 camber: -2
 caster: 16
 toe: -2

kickup bushing
1
 up down

ride height: 28 mm

:: Rear Suspension

anti-roll bar:

2.2 - black
 2.5 - silver
 2.8 - gold

wheelbase:
 long
 medium
 short

camber: -2
 toe: 3

hub:
 upper
 lower

anti-squat bushing
2
 up down

ride height: 28 mm

:: Front Shocks

spring: Silver piston: 10 x 1.1 Tapered
 shock fluid: 25 Wt length: 106.5 mm
 shock cap: Stock

:: Rear Shocks

spring: Black piston: 10 x 1.1 Tapered
 shock fluid: 27.5 Mixed Wt length: 125 mm
 shock cap: Stock

:: Differentials

front fluid: 5000
 center fluid: 5000
 rear fluid: 5000

:: Wing

location: forward back
 angle: low med. high
 type: MP9 (25mm Gap)

:: Chassis Braces / Wheel Hex

chassis braces:
 standard molded aluminum
 wheel hex:
 standard narrow

:: Electronics

motor & wind: N/A
 esc: LRP SX8 setting: 1/1/2/0
 batteries: Orion 5000 20C
 radio: Airtronics M11x
 steering expo: 0%
 brake e.p.a.: 83%
 throttle expo: 0%
 servo: Airtronics
 initial brake: _____ drag brake: _____

:: Gearing

pinion gear: 15
 spur gear: 46

:: Tires

tire (F/R): Proline Caliber / Proline Caliber
 compound (F/R): M3 / M3
 insert: Proline Evo wheel: Associated 83 mm
 traction additive: N/A

:: Race and Vehicle Comments

qualify: 1 main: A finish: 1 tq:
 comments: No Front Shock Boots; No Front Sway Bar; RC8B Shock Towers: Front #4,
Rear #7; RC8B Steering Link; RC8B Suspension Mounts; 16mm Shocks

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____