BLACKBOX 410R

ELECTRONICS SET-UP SHEET

Voltage input:	3.7 - 7.4/ 1-2 LiPo
On resistance (Ω)	0.00035 x2
Continuous current (A)	150
Weight without wires (g)	49
Motor limit (2-pole/4-pole)	3.5T/4800kV
SBEC	5.5 - 7.0V/5A

DRIVER: _____ EVENT: _____ TRACK: _____ DATE: _____

VEHICLE: _____ CONDITIONS: _____ BATTERY: _____ TEMP: _____

ESC INFO

FIRMWARE:	
CAPACITOR TYPE:	
FAN (YES/NO):	
WIRE SIZE:	
PROFILE #:	

BRAKE

DRAG BRAKE:	
BRAKE FREQ:	
BRAKE STRENGTH:	
BRAKE CURVE:	

SPD SENS BRAKE

LOW SPEED STR:	
HIGH SPEED STR:	
SWITCHOVER RPM:	

THROTTLE

THROTTLE FREQ:	
THROTTLE PUNCH:	
THROTTLE CURVE:	
DEAD BAND:	

MOTOR POWER

ACCEL BOOST

START RPM:	
FINISH RPM:	
MAX ADV TIMING:	

TOP SPEED TIMING

SLEW RATE:	
MAX ADV TIMING:	
DELAY TIME:	

MISC CONTROL

RUN MODE:	
MOTOR TYPE:	
SBEC VOLTAGE:	
FORWARD POWER:	
REVERSE POWER:	

PROTECTION

BATTERY CUTOFF:	
ESC TEMP CUTOFF:	

MOTOR SETTINGS

MOTOR:	
WIND:	
TIMING:	
ROTOR:	
FDR/ROLLOUT:	
TEMPERATURE:	

RADIO SETTINGS

THROTTLE EPA:	
BRAKE EPA:	
THROTTLE EXPO:	
BRAKE EXPO:	

NOTES:

_____

REEDY POWERED

www.ReedyPower.com

www.facebook.com/ReedyPower

twitter.com/ReedyPower

IFMAR WORLD CHAMPIONS 29 TIME REEDY